



CR1275

Content	1275 cc
Top out	218x154 mm
Top in	202x138 mm
Bottom	182x119 mm
Useful Height	48 mm
Height	51 mm
Nett weight	15,40 gr
Thickness	75 µm
Alloy	3003 H19/3005 H18
Lubrication	300-400 gr/m ²

Packaging	Quantity ctn	Dimensions Ctn			Tare Ctn (kg)	Net Ctn (kg)	Gross Ctn (kg)	Ctn/Layer	Layer/Pal	Ctn/Pal	Quantity palet	Height Pal (m)	Gross Pal (kg)
		L(mm)	W(mm)	H(mm)									
5 x 100	500	425	350	470	0,77	7,70	8,47	6	4	24	12.000	2,03	223,28

Made of materials that complies with :

- * Regulation **2004/1935/EC** on material and articles intended to come into **contact with food** and repealing Directive 89/109/EEC
- * European Standard **EN602** "Aluminium and aluminium alloys - Wrought products - Chemical composition of semi products used for the fabrication of articles for use in **contact with food** (Version 07/2004)"

Lubrication complies with :

- * US Food and Drug Administration FDA21 CFR Ch1 § 172.830 or 178.3910 or 178.3570

Proper conditions of transport and storage

- * Long-term storage at 12-24°C and short-term transport at 10-35°C, in an atmosphere as dry as possible
- * Avoid moisture (wetness, condensation, ...) and store in closed room as dry as possible.
- * Allow 2-3 days in intermediate storage, when moving from cold to warm or damp processing rooms.

Remarks

- * Aluminium is a non-toxic metal.
- * It is recommended to avoid strongly acid and/or saline products
- * Filling material producer should judge the suitability of the packaging material for each used purpose