

# TECHNICAL SHEET

## LID AK CH2200-300

Content	- cc
Length	305 mm
Width	202 mm
Depth	- mm
Nett weight	23,71 gr
Temp	max 80 °C

Material composition	PE : 14gr/m <sup>2</sup> Cardboard : 272gr/m <sup>2</sup> PE : 18gr/m <sup>2</sup> ALU 99% : 21gr/m <sup>2</sup> - thickness 8μ PE : 56gr/m <sup>2</sup>
----------------------	--

Packaging	Quantity ctn	Dimensions Ctn			Tare Ctn (kg)	Net Ctn (kg)	Gross Ctn (kg)	Ctn/Layer	Layer/Pal	Ctn/Pal	Quantity palet	Height Pal (m)	Gross Pal (kg)
		L(mm)	W(mm)	H(mm)									
300	300	310	220	205	0,18	7,11	7,29	13	3	39	11.700	0,77	304,43

**Made of materials that complies with EC 1935/2004, and is assured by :**

- \* Using raw materials approved and suitable for food packaging, by documentation, to comply with relevant food contact legislation.
- \* Verifying that overall and specific migration components from the packaging are within an acceptable limit.
- \* Verifying that the sensory properties of the packaging does not influence the food product.

**Produced in conformity with CE 2023/2006 on good manufacturing practice for materials and articles intended to come into contact with food.**

- \* This is assured by the implemented quality assurance systems, the quality control systems and the appropriate documentation control.

**Traceability**

- \* Each box is provided with a label indicating info for traceability.

**Proper conditions of transport and storage**

- \* Long-term storage at 12-24°C and short-term transport at 10-35°C, in an atmosphere as dry as possible
- \* Avoid moisture (wetness, condensation, ...) and store in closed room as dry as possible.

**ATTENTION : REMOVE LID FROM CONTAINER BEFORE HEATING CONTAINER IN OVEN, MICROWAVE, ...**